


# MOLYDUVAL Inox Spray



## Metallic Corrosion Protection based on V2A

An air drying coating, with a base made of stainless steel particles and high temperature resistant resins. Designed for protecting steel and iron elements which get a metal appearance. Its special formulation allows temperatures higher than 450°C and even non-lasting risings up to 650°C.

### Properties

- \* strong tackiness
- \* very good corrosion protection
- \* suitable for very high temperatures
- \* fast drying
- \* rejects dirt
- \* may hardened by burning in

### Applications

- \* for preservation of thermic loaded exhaust pipes, heat exchangers, refrigeration equipment
- \* for coating metals
- \* for protection of steel and iron parts
- \* for preservation of steel and iron parts after welding, steel bridges, balustrades, scaffoldings, bridges, gateways

### Technical Datas

Color		silver-grey
Temperature Range	°C	650
Unit	ml	400

*The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.*

For further information, please see our website [www.molyduval.com](http://www.molyduval.com) or consult your local representative.

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product to ensure that the product is safe, effective and fully satisfactory for the intended end use. It does also not form part of any sales contract as guaranteed properties of the delivered material.