

MOLYDUVAL

Sekorex IL Spray



Chain Drive Pin Lubricant

A high treated low viscosity penetrating oil for chains. Penetrates between the close clearance of the chain drive bushings and pins to provide lubrication. For chains in assembly lines, machinery, fork lifts, conveyers.



Properties

- * free of silicones
- * excellent wear protection
- * good low temperature characteristics
- * low evaporation
- * extremely high penetrative properties
- * low viscosity
- * very long-time stable
- * infiltrates humidity
- * very thin film
- * good penetrative properties
- * penetrates between the clearance of chain drive
- * cleans the chain, looses dirt



Applications

- * for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- * for chains in textile industry
- * for chains in precision engineering
- * for bicycle chains



Technical Datas

Color		brown
Viscosity 20°C	mm ² /s	4
Density 15°C	kg/m ³	830
Temperature Range	°C	-30 -> +80
Pour Point	°C	-60
Flash Point	°C	63

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For more technical information contact us !

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. It does also not form part of any sales contract as guaranteed properties of the delivered material.